



D9180

Printing Results


High-Speed & High-Quality



Vibrant Color Screen



Extreme Wear
Resistance



Prints Super-Small
(15mm label)



Compliant with multiple certifications: 3C CE FCC RoHS



D9180

Dimensions(DxWxH)
205.5X146X143mm

Print Head Durability
50km

Certification
CE

Weight
1.62kg

1.5" Color Screen
Jumbo Roll Capacity
Visible Paper Tray
Rear-Load
Large Gears
Less Wear
Longer Life
Easy to Use

Printing Method

Thermal (Direct Thermal)

Printer Command languages

ESC , TSPL

Heater Resolution

203dpi

Print Width

80mm

Interface

USB(standard); USB Bluetooth(optional); USB WiFi(optional);
USB Serial Port Ethernet(optional)

Media Width

15-85mm (With liner)

Media Type

Thermal sensitive bill paper;
Thermal sensitive bill paper
thermal sensitive black label
paper (back)

Character Scaling/Rotation

Acalable Front. Rotation: 0°,
90°, 180°, 270°

Paper Roll Core Inner Diameter

25.4 mm

Max. Roll Outer Diameter

100 mm

Direction

Front delivery

Power Input

DC24V 1.5A

Operation Environment

5°C to 45°C, 20% to 90%
RH (non-condensing)

Storage Environment

-20°C to 55°C, 20% to
93% RH (non-condensing)

Print Speed

- 152mm/s
- Upgradable to 200mm/s
- High-speed printing with smooth paper feeding
- Toggle-Type Paper Jam Release Lever
- Auto-centering printing
- Supports smaller labels
- Automatic media detection
- (Instantly recognizes loaded paper/media)
- Crisp print quality | Stable performance