

# PT-280

## Mobile Thermal Printer



### ■ Feature

- \* Mobile suited for outdoor usage
- \* Black mark paper location sensor
- \* Low battery indicator(18650 type , 3.7V 2000mAh)
- \* Equipped with lithium battery for 8 hours continuous work
- \* Vairous interface and capabilites
- \* Bluetooth high communication speed
- \* High printing speed , up to 90mm/s.



## Application



- \* Medical Equipment
- \* Mobile POS/Retail
- \* Hospitality
- \* Packing citation
- \* Deliveries

- \* Onboard Transportation
- \* Field reports/Installation
- \* Warehouse/ logistics
- \* Utility billing/meter reading

## Specification

Model	PT-280
Dimension	100*75*47mm (W*D*H)
Print method	Thermal
Paper width	58mm
Print width	48mm
Weight ( g)	199g
Max diameter of paper roll	40mm
Dot per lie	384 dots/line
Print speed	90mm/s
Life cycle time	50km(printing density under 12.5%)/100 million pulses
Text and graphic Support	English, figure, symbol, Chinese, graph, curve, icon pre-stored, barcode (CODE39,EAN13, EAN8 CODABAR, CODE128, CODE93ITF), 2D : QR code ,PDF417
Dot pitch (resolution)	203DPI/8 dots/mm
Interface	USB (support USB charging ) Bluetooth support: Android+iOS
Power	2000mAh 3.7 V rechargeable Lithium battery (2600mAh/3000mAh optional) Battery type: 18650 lithium battery
Recharge adapter	Stand by recharging / AC adapter
Self-check	Without paper /low power/ cover open
Black mark test	Supported
Commands	ESC/POS compatible with command sets
Paper cut	By manual
Operate setting	Temperature:-10°C~50°C; Humidity:20%~85%
Recharge Setting	Temperature:5°C~40°C; Humidity:20%~85%
Storage Setting	Temperature:-20°C~70°C; Humidity:5%~95%
Standard accessories	Long-term preservable paper, AC adapter, Li-ion battery
Certificate	CE , FCC , BIS