

PT-380

Mobile Thermal Printer



■ Product Features

- * Support 100mm/s fast printing;
- * Supports customized vector font printing and changing vector fonts;
- * Provide original SDK and online software integration support;
- * 2600mAh durable battery equipped with sleep mode and other functions;
- * Device functions are able to be set up by Keypads & OLED display quickly;
- * Adopting a sliding paper guide to lock various consumables;
- * IP54 Protection Grade and passed 1.2M drop test;
- * Optional waist clip, strap accessories.



■ Specification

Model	PT-380
Print Method	Direct thermal
Command	TSPL (default), CPCL
Resolution	203DPI
Print Speed	100mm/s (Max. continues paper) 70mm/s (Max. label paper)
Print Width	72mm
Print Head Temperature Detect	Thermistor
Print Head Position Detect	Mircoswitch
Media Sensor	Reflective & Transmissive Sensor
Sensor position	On the left side
LED display	128X640LED
Keypad	Power / Save,Feed / Set, Menu
Interface	USB+Bluetooth
USB Port	Type-C
USB VID PID	VID: 0471 PID: 0055
Max. printed contents	72mmX300mm
Graphics	Support Single color PCX, BMP image file
Barcode	QRCODE、PDF417
Character Set	Common single byte fonts: FONT 0 to FONT 8 Simplified Chinese (GB18030: 16x16, 20x20 Traditiona Chinese (BIG5): 24x24 Korean Support printing with specified vector fonts
Character Enlargement/Rotation	TSPL: Both horizontally and vertically can be magnified by 2-30 times CPCL: According to the CPCL standard, it can be enlarged horizontally and vertically, 96x96'(MAX) Conditioners (0°、90°、180°、270°)
PaperType	Continuous thermal paper, label paper, back marker paper
Media Width Media	25-80mm
Thickness	0.06mm-0.17mm
Media roll diameter	51mm
Paper Feeding	Top feeding
Power Supply	Input: DC 5V 2A
Recharge time	≤ 3h
Standby time	≥ 96h
Printing capacity	≥ 200 meters (12.5% Printing rate at 25°C)
Battery cycle life	500次, ≥ 80%
Battery Capacity	7.4V/2600mAh
Work Environment	-10°C~50°C, 20~90%RH
Storage Environment	-20°C~60°C, 20-93%RH
Net Weight	250g
NetWeight (with battery)	360g
Dimension	114mm x 112mm x60mm